

HD-RX-101-C-1G-E-B-T

DM Lite – HDMI® over CATx Receiver, Wall Plate, Black Textured

- > Pairs with a DM Lite transmitter to provide a simple point-to-point signal extender
- > Enables extension of HDMI® video and audio signals
- > Links to the transmitter via a single CAT5e (or better) twisted pair cable^[1]
- > Supports 4K and UHD at up to 130 ft (40 m)
- > Supports HD 1080p, WUXGA, and 2K at up to 230 ft (70 m)
- > Handles 4K video resolutions up to 4K60 4:2:0 and 4K30 4:4:4
- > Handles 3D video and Deep Color
- > Supports Dolby® TrueHD, Dolby Atmos®, DTS HD®, DTS:X®, and uncompressed 7.1 linear PCM audio
- > Compatible with HDMI and DVI display devices^[3]
- > HDCP 2.2 compliant
- > Passes CEC and EDID signals
- > Flush wall mount design
- > Installs in a single-gang U.S. electrical box (2-1/4" deep) or plaster ring
- > Decorator style faceplates sold separately
- > Normally powered by the transmitter (surface mount) over the link cable^[2]
- > Universal 100-240V power pack available separately (coming soon) for use with a wall plate transmitter^[2]

The **HD-RX-101-C-1G-E-B-T** is a wall plate DM Lite receiver designed to pair with a DM Lite transmitter to form a point-to-point signal extender for HDMI® signals. The DM Lite family of products offers a very simple and versatile solution for extending HD, UHD, 2K, and 4K video signals, with stereo or surround sound audio, over a single CAT5e (or better) cable. A cable length of up to 230 ft (70 m) is supported for HD 1080p, WUXGA, and 2K signals, or up to 130 ft (40 m) for UHD and 4K.^[1]

*For applications requiring a surface mount version, refer to the **HD-RX-101-C-E**.*

*For applications that require IR or RS-232 signal extension, refer to the **HD-RXC-101-C-1G-E-B-T**.*

The HD-RX-101-C-1G-E-B-T is designed to mount in a single-gang electrical box or plaster ring (not included). It is normally powered by the transmitter over the link cable when using a surface mount transmitter. If using a wall plate transmitter, a single power pack must be purchased (sold separately, model TBA), which may be connected to either the receiver or transmitter.^[2]

Important: This product is not addressable from a control system and offers no programmable functionality. AV and CEC signals are simply passed through between a single transmitter and receiver pair. The RJ45 link port on this product is exclusively intended for linking with a single DM Lite transmitter. It should not be used to connect to any other equipment or network. DM Lite is not compatible with PoE, PoDM, DigitalMedia 8G+® (DM 8G+®), or HDBaseT®.



Faceplate
sold separately

SPECIFICATIONS

Video

Output Signal Type: HDMI w/Deep Color, 3D, & 4K (DVI compatible^[3])
Copy Protection: HDCP 2.2

Maximum Resolutions:

Scan Type	Resolution	Frame Rate	Color Sampling	Color Depth
Progressive	4096x2160 DCI 4K & 3840x2160 4K UHD	24 Hz	4:4:4	30 bit
		30 Hz	4:4:4	24 bit
		30 Hz	4:2:2	36 bit
		60 Hz	4:2:0	24 bit
	2560x1600 WQXGA	60 Hz	4:4:4	36 bit
	1920x1080 HD1080p	60 Hz	4:4:4	36 bit
Interlaced	1920x1080 HD1080i	30 Hz	4:4:4	36 bit

NOTE: Common resolutions are shown; other custom resolutions are supported at pixel clock rates up to 300 MHz

Audio

Output Signal Type: HDMI

Formats: Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos, DTS®, DTS ES, DTS 96/24, DTS HD High Res, DTS HD Master Audio, DTS:X, LPCM up to 8 channels

HD-RX-101-C-1G-E-B-T DM Lite – HDMI® over CATx Receiver

Communications

HDMI: HDCP 2.2, EDID, CEC pass-through

DM Lite Link: Proprietary link for connection between one DM Lite TX & RX only

Connectors

HDMI OUT: (1) HDMI Type A connector, female;
HDMI digital video/audio output (DVI compatible^[3])

FROM TX (rear): (1) 8-pin RJ45 connector, female, shielded;
Link port for connection to a DM Lite transmitter^[1]

24VDC 1.25A (rear): (1) 2-pin 3.5 mm detachable terminal block;
24 Volt DC power input;

Power pack sold separately (if required, model TBA)^[2];

*Note: This connection powers both the receiver and transmitter;
this connection is not normally used when pairing with a surface
mount transmitter.^[2]*

Indicators

PWR: (1) Green LED, indicates operating power is supplied from the TX
via the DM Lite link or from a power pack via the 24VDC input

HDMI OUT: (1) Green LED, indicates HDMI output signal presence

FROM TX: (2) LEDs (on RJ45 connector), green LED indicates link status,
amber LED indicates a valid video signal

Power

Power Pack (sold separately): Input: 100-240 Volts AC, 50/60 Hz;
Output: 1.25 Amps @ 24 Volts DC;
Model: TBA

*Note: This power pack is only required when pairing with a wall plate
transmitter. When pairing with a surface mount transmitter, use the power
pack supplied with that transmitter. The receiver and transmitter are
powered together using a single power pack connected at either the
receiver or transmitter (not both).^[2]*

Environmental

Temperature: 32° to 104° F (0° to 40° C)

Humidity: 20% to 90% RH (non-condensing)

Construction

Composition: Metal housing and bracket with black polycarbonate front
label overlay

Mounting: Mounts in a 1-gang (or larger) 2-1/4 inch (57 mm) deep U.S.
electrical box or plaster ring (not included)

Faceplate: Requires a decorator-style faceplate (FP-G series,
sold separately)

Dimensions

Height: 4.08 in (104 mm)

Width: 1.81 in (46 mm)

Depth: 1.97 in (50 mm)

Weight

5.22 oz (148 g)

Compliance

UL Listed for US & Canada, CE, IC, FCC Part 15 Class B digital device

Maximum DM Lite Link Cable Lengths

Cable Type:	CAT5e (or better), DM-CBL-ULTRA DM® Ultra Cable, or DM-CBL-8G DM 8G® Cable ^[1]
Resolution:	
1920x1080 FHD 1080p	230 ft (70 m)
1920x1200 WUXGA	
1600x1200 UXGA	
2048x1080 DCI 2K	
2048x1152 QWXGA	
2560x1080 UWFHD	130 ft (40 m)
2560x1440 WQHD	
2560x1600 WQXGA	
3840x2160 4K UHD	
4096x2160 DCI 4K	

MODELS & ACCESSORIES

Available Models

HD-RX-101-C-1G-E-B-T: DM Lite – HDMI® over CATx Receiver, Wall Plate,
Black Textured

Available Accessories

FP-G1-B-T: Decorator Style Faceplate, 1-Gang, Black Textured

HD-TX-101-C-1G-E-B-T: DM Lite – HDMI® over CATx Transmitter, Wall
Plate, Black Textured

HD-TX-101-C-1G-E-W-T: DM Lite – HDMI® over CATx Transmitter, Wall
Plate, White Textured

HD-TX-101-C-E: DM Lite – HDMI® over CATx Transmitter, Surface Mount

HD-TX-201-C-2G-E-B-T: DM Lite – HDMI® over CATx Transmitter & 2x1
Auto-Switcher w/VGA & Analog Audio, Wall Plate, Black Textured

HD-TX-201-C-2G-E-W-T: DM Lite – HDMI® over CATx Transmitter & 2x1
Auto-Switcher w/VGA & Analog Audio, Wall Plate, White Textured

HD-TX-301-C-E: DM Lite – HDMI® over CATx Transmitter & 3x1 Auto-
Switcher w/2x HDMI plus VGA & Analog Audio, Surface Mount

HDI-TX-301-C-2G-E-B-T: DM Lite – HDMI® over CATx Transmitter & 3x1
Auto-Switcher w/2 HDMI plus VGA & Analog Audio, UK/European Wall Plate,
Black Textured

HD-RX-101-C-1G-E-B-T DM Lite – HDMI® over CATx Receiver

HDI-TX-301-C-2G-E-W-T: DM Lite – HDMI® over CATx Transmitter & 3x1 Auto-Switcher w/2 HDMI plus VGA & Analog Audio, UK/European Wall Plate, White Textured

DM-CBL-ULTRA-PC Series: DigitalMedia™ Ultra Patch Cables

DM-CONN-ULTRA-RECP Series: DigitalMedia™ Ultra Keystone RJ45 Jacks

DM-RPP-K24: DigitalMedia™ 24-Port Keystone Patch Panel

DM-CBL-8G-NP Series: DigitalMedia 8G™ Cable, non-plenum

DM-CBL-8G-P Series: DigitalMedia 8G™ Cable, plenum

DM-8G-CONN-WG: Connector with Wire Guide for DM-CBL-8G

DM-8G-CRIMP-WG: Crimping Tool for DM-8G-CONN-WG

DM-CBL-ULTRA-NP Series: DigitalMedia™ Ultra Cable, Non-Plenum Type CMR

DM-CBL-ULTRA-P Series: DigitalMedia™ Ultra Cable, Plenum Type CMP

DM-CBL-ULTRA-LSZH Series: DigitalMedia™ Ultra Cable, Low Smoke Zero Halogen (Available only in Europe)

DM-CONN-20: Connectors for DM-CBL-ULTRA DigitalMedia Ultra Cable
CBL Series: Crestron® Certified Interface Cables

Notes:

1. For the DM Lite link cable, use Crestron [DM-CBL-8G](#) DigitalMedia 8G™ cable, Crestron [DM-CBL-ULTRA](#) DigitalMedia™ Ultra cable, or third-party CAT5e (or better). The maximum cable length is 230 ft (70 m) for resolutions up to 2K or 130 ft (40 m) for higher resolution signals up to 4K. Refer to the "Maximum DM Lite Link Cable Lengths" table for a more detailed overview. Shielded cable and connectors are required when bundling multiple cables in a wire run, and are recommended for all applications to safeguard against unpredictable environmental electrical noise which may impact performance at resolutions above 1080p. All wire and cables are sold separately. DM Lite devices are not compatible with DigitalMedia 8G+ (DM 8G+), HDBaseT, PoE, PoDM, or any other CATx based interface or network.

2. When connecting a wall plate receiver to a surface mount transmitter, use the power pack that ships with the transmitter. If the receiver and transmitter are both wall plates, a separate power pack must be purchased, which may be connected to either the receiver or transmitter. Only one power pack is required. Do not connect more than one power pack. Please note, the wall plate compatible power pack is not yet available. Please contact Crestron [Customer Support](#) for assistance when pairing a wall plate receiver with a wall plate transmitter. DM Lite devices are not compatible with PoE or PoDM.
3. The HDMI output requires an appropriate adapter or interface cable to accommodate a DVI signal. [CBL-HD-DVI](#) interface cables are available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at <https://www.crestron.com/How-To-Buy/Find-a-Representative> or by calling 855-263-8754.

The specific patents that cover this and other Crestron products are listed online at <https://www.crestron.com/legal/patents>.

Certain Crestron products contain open source software. For specific information, please visit <https://www.crestron.com/opensource>.

Crestron, the Crestron logo, DigitalMedia, DigitalMedia 8G, DigitalMedia 8G+, DM, DM 8G, and DM 8G+ are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby, Dolby Atmos, and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS HD, and DTS:X are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDBaseT is either a trademark or registered trademark of HDBaseT Alliance in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.
©2018 Crestron Electronics, Inc.

