STATUS:
JAB 01/05/2015 - RELEASED ON ECO: 500011246

TECH-000604







RAILS CAN BE SLID LEFT OR RIGHT
FOR OFFSET

1. MAXIMUM MOUNTING PATTERN IS 22.7" (576 mm) WITHOUT REVERSING UPRIGHTS
2. MAXIMUM MOUNTING PATTERN IS 25.3" (642 mm) WITH REVERSING UPRIGHTS
3. FOR RECESSED APPLICATIONS, MINIMUM VERTICAL LIFT FOR HOOK ENGAGEMENT IS .75" (19) mm)

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF MILESTONE AV TECHNOLOGIES NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF MILESTONE AV TECHNOLOGIES.

CAD GENERATED DRAWING.
DO NOT MANUALLY UPDATE.

DRAWN BY	JAB	4/8/2014
ENG APPROVAL		
MFG APPROVAL		
QA APPROVAL		

SHEET 1 OF 1 | SCALE 1:8 | SIZE B | DWG. NO. TECH-000604 | REV. 01

CHIEF
6436 CITY WEST PKWY
EDEN PRAIRIE MN, 55344
PHONE: 866-977-3901
FAX: 877-894-6918

DESCRIPTION
MSM1U CUSTOMER TECHNICAL DRAWING

MODEL NO.
MSM1U